



ULTRASHIELD BIO-ACTIVE

ACTIVE

Quick Acting Bio-Enzymatic Activator, Efficiency Booster and Odour Control for Septic Tanks and Cess Pits THE NATURAL, SAFE, NON-POLLUTING WAY TO BOOST SEPTIC TANK ACTION

For improving the performance of Septic Tanks and Cess Pits - cuts rate of solids build-up and cost by reducing emptying frequencies. Ideal for Country Hotels, Farms, Rural Homes, Campsites and Static Home Parks (5% of UK homes are served by waste tanks.)

- Effective control of foul odour problems - important in hot weather with shared systems, old or shallow fall systems, foul pipe 'backing-up' into hotel kitchens or toilets, where neighbouring properties are situated nearby.
- A natural and environmentally responsible method of preventing blockages - this special compound of bacteria enzymes and nutrients are designed to degrade the principal sources of blockages - grease and paper (cellulose).
- Reduces the rate of solids build-up (by increasing the rate of bio-degradation) - thus the frequency of excessive tanker emptying can be cut by up to 300%.

ACTION

UltraShield Active is a safe, natural and environmentally responsible way to manage waste tank function. Septic Tanks and Cess Pits degrade and mineralise waste organic matter. Part of the waste they receive e.g. grease and paper, is difficult to degrade and it accumulates and reduces the effectiveness of the tank. The micro-organisms in **UltraShield Active** are specially selected for their ability to degrade grease, cellulose and waste. They are protected from bleaches and disinfectants and rapidly enhance the biological action of the Septic Tank.

APPLICATION

Pour the appropriate dosage of **UltraShield Active** into the toilet bowl and flush

COMPOSITION

UltraShield Active is a compound of nutrients, starter enzymes and selected strains of micro-organisms able to degrade organic waste, organo-sulphur compounds and cellulose

For start-up, or to treat overloaded septic tanks suffering from blockages and foul odours 50 grams per cubic metre of septic tank (4 persons) for two consecutive days.

Maintenance Dose. 25 grams (approx.1 tablespoon) per cubic metre of septic tank once every week.

Envirobridge Technologies

Suite 33 29/30 Horsefair
Banbury Oxfordshire OX16 0BW
United Kingdom
Tel: +44(0)1295 780444
Mob: +44(0)7968 179272
Email: info@ultrashielduk.co.uk

